

PLEASE SPECIFY THE FOLLOWING WHEN ORDERING MOTORIZED SYSTEMS

1. Type of system or window treatment to be motorized.
2. Is measurement provided for “Inside Measure” (IM) or “Outside Measure” (OM)?
IM deduction on D-8 Headrail, Drapery Track and Vertical Track is ½”
IM deduction on Roller Shade is ¼”
3. Which side (end) of Headrail is power cord?
Which end of drapery track is motor mounted?
4. For D-8 Headrail: specify headrail color, lift tape and ladderbraid color.
5. For Drapery or Vertical Track: specify: OPENING (in the direction of) :
One-way left, (OWL); One-way right,(OWR); Center Opening (CO); or Off set,
(OS).
6. Type of pleating on drapery. (Pinch Pleat, S-Fold, Z-Fold). Accordiafold / Ripplefold
7. Ceiling or wall mount.

CONTROL

8. Specify: Motor is to be operated by:
Wall Switch - 110 volt AC line voltage switch
Dry Contact Switch - In-wall or panel mounted switch
Radio Remote - single or multiple channel wireless remote control with or without
override
Infrared Remote - Handheld remote, TouchPad. eye, or stand-alone eye
9. Number of motors to be operated from individual control(s)
10. Length of cord from motor to receiver Drapery Track Standard length. 6 ft.
(D-8 receiver fits inside headrail)
11. Length of cord from receiver to 110 Volt AC outlet. Standard length 14 ft.